



STEAM GENERATORS

SG-20/SG-30

PRESSURE

5,0-5,5
bar

FLOW RATE

80-100
g/min

ABSORBED POWER

3,0
kW



SG-20



SG-30 - BOILER WITH AUTO-FILLING TANK

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ LONG LIFE

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS




LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

TECHNICAL DATA

| | | SG-20 S 5008 M | SG-30 S 5510 M |
|-----------------------|---------|-----------------------|-----------------------|
| Code | | GNVA40016 | GNVA40017 |
| PERFORMANCE | | | |
| Operating pressure | bar/Mpa | 5/0,5 | 5,5/0,55 |
| Steam flow rate | g/min | 0-80 | 0-100 |
| Max steam temperature | °C | 140 | 140 |
| Start up time | min | ~ 7 | ~ 7 |
| Power supply | Ph-V-Hz | 1-230-50 | 1-230-50 |
| Max absorbed power | kW | 3 | 3 |
| Boiler volume | l | 2,2 | 2,2 (auto-filling) |
| Water tank | l | 2 | 2 |
| Dimension (LxWxH) | cm | 57x40x65 | 57x40x65 |
| Weight | kg | 11,5 | 12 |

STANDARD EQUIPMENT

CODE: IPIP45757
**HANDGRIP + HOSE
 STEAM/SUCTION MT 2,5
 (FOR SG-20)**



CODE: IPIP40001
**HANDGRIP + HOSE
 STEAM/SUCTION MT 2,5
 (FOR SG-30)**



CODE: KTRI40277
**ACCESSORIES KIT
 STEAM/SUCTION**



OPTIONAL ACCESSORIES

CODE: IPIP47898
**HANDGRIP + HOSE
 STEAM 2,5MT
 (OPTIONAL FOR SG-20)**



CODE: IPIP45815
**HANDGRIP + HOSE
 STEAM 5MT
 (OPTIONAL FOR SG-30)**



CODE: KTRI40275
**STEAM ONLY
 ACCESSORIES KIT**



CODE: KTRI89496
TROLLEY



CODE: KTRI40269
**DESCALING KIT
 (10 PHIALS)**

